



Back illuminated mirror.



- Lighting: LED.
- Absorption: OKAT07 = 12 W / OKAT08 = 21 W / OKAT10 = 33 W / OKAT09 = 44 W.
- Switch: please arrange a control switch.
- Colour temperature: 3000 K.
- Voltage: 110 ÷ 240 V - 50 ÷ 60 Hz (Europe/USA).

	L	P	H	
Europe/USA version. ....	520	56	520	<b>OKAT07</b>
Europe/USA version. ....	800	56	800	<b>OKAT08</b>
Europe/USA version. ....	1200	56	1200	<b>OKAT10</b>
Europe/USA version. ....	1600	56	1600	<b>OKAT09</b>


Back illuminated mirror.



- Rear support: aluminium frame.
- Lighting: LED.
- Absorption: OKGL01 = 21 W / OKGL02 = 37 W / OKGL03 = 37 W / OKGL04 = 51 W.
- Switch: please arrange a control switch.
- Colour temperature: 3000 K.
- Voltage: 110 ÷ 240 V - 50 ÷ 60 Hz (Europe/USA).

	L	P	H	
Europe/USA version. ....	900	56	900	<b>OKGL01</b>
Europe/USA version. ....	1200	56	900	<b>OKGL02</b>
Europe/USA version. ....	1400	56	900	<b>OKGL03</b>
Europe/USA version. ....	1800	56	900	<b>OKGL04</b>


Mirror without lighting.



- Melamine-coated rear support.

	L	P	H	
.....	520	56	520	<b>OKAS01</b>
.....	800	56	800	<b>OKAS02</b>
.....	1200	56	1200	<b>OKAS04</b>
.....	1600	56	1600	<b>OKAS03</b>

Mirror without lighting.



- Rear support: aluminium frame.

	L	P	H	
.....	900	56	900	<b>OKGS01</b>
.....	1200	56	900	<b>OKGS02</b>
.....	1400	56	900	<b>OKGS03</b>
.....	1800	56	900	<b>OKGS04</b>